

# Ampacoll® ND duo

Nail sealing tape for roofs and formwork strips



external

- Better adhesion than many customary nail sealing products
- Closed-cell foam, PVC-free
- Adhesive on both sides – ideal for prefabrication
- HFA leak detection tests (Holzforschung Austria)

## Technical details

Shelf life	2 years
Storage	Cool and dry
Application temperature	from 0 °C
Resistance to temperature	-25 °C to +75 °C
Outdoor weathering period	3 months
Resistance to ageing	> 20 years

**Area of application:** Double-sided, self-adhesive nail sealing tape for roofs and formwork strips. Prevents humidity from penetrating the construction. Particularly well suited for prefabrication.

# 10

Jahre Garantie  
Ans Garantie  
Anni Garanzia  
Years Warranty

Security is part of the system at Ampack. We not only cover the cost of the materials, but also the installation and removal costs.

✓ **HFA-tested**

Leak detection tests of Holzforschung Austria

**ISO 9001**  
Swiss Research

## Delivery forms

Item no.	Identification	Roll size	Box contents	Pallet contents
7640115533951	Ampacoll® ND duo	30 m × 60 mm × 3 mm	8 rolls = 240 m <sup>1</sup>	18 boxes



### Other nail sealing products



**Ampacoll® ND 60:**  
Nail seals, 60 mm wide



**Ampacoll® ND 80:**  
Nail seals, 80 mm wide



**Ampacoll® ND.Band 60/80:**  
Adhesive nail sealing tape 60/80 mm wide



### Application tips

#### The protective function of a nail seal

What good is the best roof membrane when water can penetrate the screw or nail holes? **Ampacoll® ND Duo** nail sealing tape is your guarantee for water-tight roof membranes. Twisted counter battens, shrinking wood, extreme alternating cycles of wet and dry, low contact pressure, poor adhesion of the nail in the rafters, mechanical loading from scaffolding or tile trestles, permanent snow coverings – these are all potential sources of damage!

#### Tips when laying

Option 1: Mark out a line for each batten and glue **Ampacoll® ND Duo** directly onto the underlay material. Then fix the battens.

Option 2: Apply **Ampacoll® ND Duo** directly to the battens. This can be carried out in the workshop. The battens can then be easily moved around on the roofing membrane and positioned correctly. The liner can be easily removed from the side, without tearing.

#### Ampack recommends

Counter battens are extremely susceptible to the extremes of wet and dry. Therefore for better insulation a nail seal is preferred to screwing the counter battens.




Please observe the recommendations for use and further system products in our adhesives matrix



Further information and detailed documentation at [www.ampack.biz](http://www.ampack.biz)

Sales via specialist dealers



The following information could have been superseded by new findings or developments. Current Information can be found at [www.ampack.biz](http://www.ampack.biz). © Ampack AG, Rorschach, 03.2018

**www.ampack.biz**  
Ampack Switzerland: 071 858 38 00  
Ampack Austria: 05523 53433  
Ampack Germany: 07621 1610264  
Ampack France: 04 50 83 70 54  
Ampack Italy: 0471 053 475

