

Ampacoll® Komprimax K

Precompressed joint sealing tape



- > Stress group 1 (BG 1)
- > Each roll separately sealed and marked
- > With delay effect
- > No variation in tape thickness
- > Reusable seal prevents swelling during storage

Technical details

Stress group	BG 1
Shelf life	12 months
Joint permeability	$a \leq 1.0 \text{ [m}^3 / (\text{h} \times \text{m} \times (\text{daPa})^{0.91}]$
Density	approx. 85 kg/m ³
Driving rain impermeability	$\leq 750 \text{ Pa}$
Temperature resistance	-20°C to +80°C
Application temperature	from -5°C
Building material class	B1



Area of application: For sealing doors and windows in solid, wood and metal constructions.

Delivery forms

Item no.	Identification	Roll size	Joint width	Box contents
7640115537904	Ampacoll® Komprimax K 10/2-6	10 mm × 12 m	2-6 mm	36 rolls = 432 metres
7640115537935	Ampacoll® Komprimax K 15/2-6	15 mm × 12 m	2-6 mm	24 rolls = 288 metres
7640115537966	Ampacoll® Komprimax K 15/5-12	15 mm × 8 m	5-12 mm	24 rolls = 192 metres
7640115537997	Ampacoll® Komprimax K 20/2-6	20 mm × 12 m	2-6 mm	18 rolls = 216 metres
7640115538024	Ampacoll® Komprimax K 20/5-12	20 mm × 8 m	5-12 mm	18 rolls = 144 metres



 Please observe our installation instructions for our window products.

 Please observe the recommendations for use and further system products in our adhesives matrix.

 Further information and detailed documentation at www.ampack.biz

Sales via specialist dealers

Ampack Swiss: 071 858 38 00
Ampack Austria: 05523 53433
Ampack Germany: 07621 1610264
Ampack France: 04 50 83 70 54
Ampack Italy: 0471 053 475



The following information may have been superseded by new findings or developments.
Current information can be found at www.ampack.biz. © Ampack AG, Rorschach, 05.2019

8008EU/DX.YY(VS)0519

www.ampack.biz