

Ampatop® B black

Wind seal for façades with open gaps



- > Withstands UV
- > 10-year product guarantee with a joint width up to 30 mm
- > Fire behaviour Euroclass B
- > Outdoor weathering of six months

Technical details		Value	Standard
s _D value		0,04 m	EN 1931
Resistance to water penetration		W1	EN 1928
Weight		210 g/m ²	EN 1849-2
Fire behaviour		B	EN 13 501-1
Tear resistance	longitudinal	300 N/5 cm	EN 12 311-1
	transverse	200 N/5 cm	
Tear elongation	longitudinal	25 %	EN 12 311-1
	transverse	25 %	
Resistance to further tearing (nail shaft)	longitudinal	120 N	EN 12 310-1
	transverse	120 N	
Outdoor weathering		6 months (before installation of façade cladding)	
UV stability		> 10 years	
Temperature resistance		- 40 to +100 °C	
5000-hour test		passed	

10

Jahre Garantie
Ans Garantie
Anni Garanzia
Years Warranty

Security is part of the system at Ampack. We not only cover the cost of the materials, but also the installation and removal costs.

CE

EN 13859-2

 **ISO 9001**
Swiss Research

5000-hour test

Tips for laying:

Ampatop® B black should be laid onto the existing support structure, taut and without any folds, with the black side outwards. It should be fastened with staples that must be invisible in the overlap area. It is advantageous to cover them with battens. Both the vertical and the horizontal overlaps should be 15 cm wide and taped down with **Ampacoll® UV**, so that it is windproof. Next the counter battens are laid, thus finally fixing the wind proofing to the support structure. Visible staples that are exposed to the weather could lead to leaks, and as such should be avoided. We recommend fixings that are at a minimum galvanized, with stainless steel being preferable. The counter battens are required to secure further work and prevent any possible weather effects (e. g. wind suction or pressure). Penetrations and connections should be bonded to make them windproof with **Ampacoll® UV**. The connection width should, where possible, be at least 10 cm. If this cannot be done, a mechanical fixing is advisable. In the case of window and external doors, **Ampatop® B black** should be made windproof with **Ampacoll® UV** on the frame and if necessary secured mechanically. We recommend that the façade cladding is installed as soon as possible. In any event, the cladding must be mounted within six months. The joint width may be up to 30 mm. The individual façade elements must be at least twice as wide. The percentage of openings must not exceed 30%.

Delivery forms

Article number	Description	Roll dimensions	Content of pallets
7640115538857	Ampatop® B black	1,5 m x 50 m = 75 m ²	28 rolls = 2'100 m ²

Ampack AG

Seebleichstrasse 50
Postfach • CH-9401 Rorschach

T +41 (0)71 858 38 00
F +41 (0)71 858 38 37

ampack@ampack.ch
www.ampack.biz