



Declaration of Performance No. DoP-31-95-01
Product name: Ampatop A black

- 1 Unique identification code of the product type:**
Ampatop A black
- 2 Intended use of the construction product as specified by the manufacturer in accordance with the applicable harmonised technical specification:**
Facade membrane in accordance with EN 13859-2
- 3 Manufacturer:**
Ampack AG
Seebleichstrasse 50
CH-9401 Rorschach
- 5 System for assessing and verifying performance consistency:**
AVCP 3
- 6 Harmonised standard: EN 13859-2:2010**
Notified bodies:
 - EFACTIS (1812)
 - FIRES (1396)
 - TSUS (1301)
 - CSTB (0679)
- 7 Declared performance:**

Key features			Performance		
	Method	Unit	Nominal value	Min	Max
Fire behaviour	EN 13 501-1	-	A2-s1,d0	-	-
Resistance to water penetration	EN 1928	Class	W 1		
Resistance to water penetration after ageing	EN 13859-1, Annex C, EN 1297, EN 1296	Class	W 1		
Water vapour permeability	EN 12572	m	0.06		
Maximum longitudinal tensile force	EN 12 311-1	N/5 cm	2,900	-800	+800
Maximum tensile force longitudinal after ageing	EN 13859-1, Annex C, EN 1297, EN 1296	N/5 cm	2,160	-800	+800
Maximum transverse tensile force	EN 12 311-1	N/5 cm	2,150	-800	+800
Maximum transverse tensile force after ageing	EN 13859-1, Annex C, EN 1297, EN 1296	N/5 cm	1,890	-800	+800
Longitudinal elongation	EN 12 311-1	%	4	-	+
Elongation after ageing	EN 13859-1, Annex C, EN 1297, EN 1296	%	5	-	+2
Transverse elongation	EN 12 311-1	%	3.2	-	+
Elongation after ageing	EN 13859-1, Annex C, EN 1297, EN 1296	%	4	-	+
Resistance to tearing lengthwise	EN 12 310-1	N	150	-10	+10
Resistance to tearing across	EN 12 310-1	N	160	-10	+10
Cold bending behaviour	EN 1109	°C	-		
Hazardous substances	Must be specified	-	None		

- 8 The performance of the product corresponds to the declared performance in accordance with number 7:**
Signed for and on behalf of the manufacturer in accordance with No. 3 Rorschach, 27 June

2025

Lukas Deschwanden, Managing Director, Ampack AG, Rorschach